



# Solid State Synchronous Excitation Control

MICROPROCESSOR-BASED CONTROLLER FOR BRUSH TYPE OR BRUSHLESS SYNCHRONOUS ELECTRIC MOTORS

Rapid | Rugged | Global

## **MX2SEP** | Solid State Synchronous Excitation Control

### INTRODUCTION



A synchronous motor functions as an induction motor during start up. Once the motor approaches full synchronous speed, the Redistart™ DC exciter induces a constant polarity to the rotor causing the motor to lock into sync. Because the rotor's field is constant and separately excited, there is no slip required to produce torque. This allows the motor to run at synchronous speed.

The Benshaw synchronous package consists of a Synchronous Excitation Package (SEP) that is connected to the rotor section in conjunction with a discharge resistor. This SEP is supplied for brush type and brushless exciters.



### **RATINGS\***

Motor: 50 - 50,000HP 200 - 1000VAC

Includes discharge resistor and synchronous excitation package for brush type or brushless motor.

Exciter: 50 - 500VDC 30 - 750A

For rotor control only: Please consult factory for details.

# <mark>Redı</mark>Start™

# **KEY FEATURES**

Synchronous motors are utilized for a number of reasons; applications that require precise motor speed, to obtain greater efficiencies and facility power factor correction. Since synchronous motors can be operated at leading power factor, they are also used to correct a facility's lagging power factor created by all the other induction motors being operated. This correction reduces the penalty a customer pays the utility company for creating poor power factor.

Synchronous motors are not sensitive to harmonic problems.

- Modular power stack design
- Solid state synchronous rotor control
- Benshaw synchronous technology
- Can be supplied with MX2 or MX3 starter control
- Modbus communication
- Stepless control
- Reduced maintenance
- Configurable output relays
- Can be added to existing equipment
- Integral bypass contactor design
- Brush type and brushless control
- Advanced synchronous motor protection
- Reduction in size compared to existing field control
- Reduces inrush while maintaining torque

# **Factory Warranty**

Benshaw offers a three year warranty on all of our solid state starters.\*

Other manufacturers limit their warranties to one year. But at Benshaw, we believe that because we build them better, we can guarantee them longer.

\* With factory startup







## **TECHNICAL SPECIFICATIONS**

### **Multiple Control Functions**

- Slip percentage
- Field apply delay
- Field forcing level
- Field forcing time
- Stop mode
- Brake level
- Dynamic braking time
- Inch field level
- Inch field application time
- Inch UTS relay delay time

### Patented Soft Start Functionality

- TruTorque ramp
  - Adjustable initial current
  - Adjustable max. current
  - Adjustable ramp time
- Current ramp
  - Adjustable initial current
  - Adjustable max. current
  - Adjustable ramp time
- Power ramp
  - Adjustable initial current
  - Adjustable max. current
  - Adjustable ramp time
- MV built-in self test (BIST)
- CYCLO converter control
- Linear/tach feedback control
- Programmable decel modes
- Adjustable kick current
- Dual ramp selection
- Voltage ramp

### Integrated Electronic Protection

- Motor thermal overload
- Phase loss
- Up to speed timer exceeded
- Low line voltage
- Instantaneous overcurrent
- Overcurrent

4

- Undercurrent
- Current imbalance
- Inline contactor fault

- Control power low
- Stack over temperature
- Motor PTC input
- Shorted or open SCR
- Disconnect fault
- Phase reversal
- RTD modules
- Low line frequency
- Residual ground fault
- Independent starting and running OL's

# Real-Time Metering and Diagnostics

- VARS
- KW hours
- Run time hours / Run time - days
- MW hours
- Phase order
- Current imbalance %
- Line frequency
- Analog input
- Peak starting current
- Analog output
- Power %
- RTD temperatures
- Real-time clock
- Last starting duration
- Ground fault current

### Eight Digital Inputs Configurable To

- Stop
- Fault
- OL reset
- Fault reset
- Bypass/inline confirmation
- Local/remote selection
- Heater enable / disable
- Brake enable/disable
- One dedicated start input
- Disconnected
- Dual ramp selection
- Slow speed

#### Six Outputs Configurable To

- Faulted
- Running
- Up to speed
- Alarm condition
- Ready condition
- Locked out
- Over/under current
- OL alarm
- Shunt trip
- Ground fault
- Energy saver indication
- Heating indication
- Slow speed forward/reverse
- DC braking

Cooloing fan

### One Analog 4-20MA / 0-10VDC Input Configurable To

One Analog 4-20MA / 0-10VDC

Current (0-200%/0-800%)

Analog input (0-100%)

KW (0-10 KW/0-100 KW)

Trip high/low level

Output Configurable To

Voltage (0-150%)

MW (0-1 MW)

Firing (0-100%)

Calibration

OL (0-150%)

# **Red***i*Start™

## SUPPORT



Benshaw is dedicated to providing comprehensive 24/7 technical support. Our support personnel provide repair, spare parts, field engineering, retrofit and training services, when and where you need us. Our experienced support team is backed by the latest diagnostics and repair tools and an extensive parts inventory to minimize downtime and maximize productivity.

- Phone support hotline (1-800-203-2416)
- · Centralized coordination of all support services
- 24-hour dispatch from our operations in Pittsburgh, PA (USA) and Listowel, ON (Canada)
- Overnight parts shipment available



# Synchronous Motor Checklist

Motor Data:
HP:
Voltage:
FLA:
Secondary Voltage:
Secondary Amps:
Select one:
Brush Type Brushless
For Use with (select one):
$\Box$ Existing starter (provide drawings & details of existing unit)
$\square$ New Benshaw starter (provide additional details for Benshaw starter as applicable)
Additional Requirements:
Power Factor Control
Enclosure Type (select one):
Additional Options (specify any pilot devices, meters, etc.):



#### Benshaw, Inc.

615 Alpha Drive Pittsburgh, PA 15238 United States Toll Free: 1-800-441-8235 Phone: 412-968-0100 Fax: 412-968-5415

### Benshaw Canada Controls, Inc. 550

Bright Street East Listowel, Ontario N4W 3W3 Canada Toll Free: 1-877-291-5112 Phone: 519-291-5112 Fax: 519-291-2595

### Benshaw - Aucom Ltd. New Zealand

**Benshaw - Aucom Ltd. International** 

- Germany
- Dubai
- Korea

www.Benshaw.com