



А

В

С

D

Ε

F

G

Н


J

Κ


М

Ν


Item	Voltage / Phase	Normal Duty Rating	Normal Duty Amps	Heavy Duty Rating	Heavy Duty Amps	Weight	Heat Loss(W)	UL/IP RATING
VFD-RSI-007-H2-4C	460V / 3φ	7.5HP / 5.5kW	12.0A	5.0 HP / 3.7kW	8.0A	7.3lb / 3.3kg	172	UL OPEN / IP20




<u>top view</u>




FRONT VIEW



BOTTOM VIEW



BACK VIEW



<u>RIGHT SIDE VIEW</u>

NOTES:

\* HD: Heavy duty type for const duty type for variable torque loa 60Hz, 100% load and default can \* Refer to product manual for a \* UL Type 1 is achieved with opt



-		

stant torque load 150%P* ND: Normal
ad 120%P* Heatloss is measured with
arrier frequency.
additional details and specifications
ptional conduit box P/N EN-101040-10

H2 SERIES VFD IP, 480V, 12A, ND IP, 480V, 8.0A, HD JL OPEN (IP20)		DATE 03/26/20		612 TA7	5238	
		01/05/22 01/06/22		550 LIS	550 BRIGHT STREET LISTOWEL ONTARIO N4W 3W3	
	SIZE DWG I	NO.	VFD-RSI-007-H2-4	4C		REV O
	SCALE:	1:1		SHEET	1 OF	1