

COOLING FANS		
	_	_

А

В

С

D

Ε

F

G

Н


J

Κ


М

Ν


ltem	Voltage / Phase	Normal Duty Rating	Normal Duty Amps	Heavy Duty Rating	Heavy Duty Amps	Weight	Heat Loss(W)	UL/IP RATING
VFD-RSI-010-H2-2C	230V / 3φ	10HP / 7.5kW	30.0A	7.5HP / 5.5kW	24.0A	7.3lb / 3.3kg	248	UL OPEN / IP20




TOP VIEW




FRONT VIEW





BACK VIEW



RIGHT SIDE VIEW

NOTES:



* HD: Heavy duty type for constant torque load 150%P* ND: Normal duty type for variable torque load 120%P* Heatloss is measured with 60Hz, 100% load and default carrier frequency.
* Refer to product manual for additional details and specifications
* UL Type 1 is achieved with optional conduit box. P/N EN-101040-10

H2 SERIES VFD 7, 240V, 30A, ND IP, 240V, 24A, HD JL OPEN (IP20)	SIGNATURES DATE DRWN. RJF 03/26/20		615 ALPHA DRIVE PITTSBURGH, PA. 15	238
	СНКО. DRP 11/17/20 ENG. DRP 01/07/22 MFG.		550 BRIGHT STREET LISTOWEL ONTARIO N4W 3W3	
	SIZE DWG NO.	VFD-RSI-010-H2-2	2C	rev O
	SCALE: 1:1		SHEET 1 OF	1