



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

VFD-RSI-040-H2-4C


DWG NO.




TOP VIEW




FRONT VIEW



BACK VIEW



RIGHT SIDE VIEW



BOTTOM VIEW



Item	Voltage / Phase	Normal Duty Rating	Normal Duty Amps	Heavy Duty Rating	Heavy Duty Amps	Weight	Heat Loss(W)	UL/IP RATING
VFD-RSI-040-H2-4C	460V / 3φ	40HP / 30kW	61.0A	30HP / 22kW	41.0A	16.5lb / 7.5kg	880	UL OPEN / IP20

NOTES:

* HD: Heavy duty type for constant torque load 150%P* ND: Normal duty type for variable torque load 120%P* Heatloss is measured with 60Hz, 100% load and default carrier frequency.

* Refer to product manual for additional details and specifications

* UL Type 1 is achieved with optional conduit box. P/N EN-101040-01

REVISIONS DO NOT SCALE DWG	THIRD ANGLE PROJECTION		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES INTERPRET DRAWING PER ASME Y14.5M-1994 TOLERANCES: .XX ± .03 .XXX ± .015 ANGLES ± 1°	TITLE: H2 SERIES VFD 40HP, 480V, 61A, ND 30HP, 480V, 41A, HD UL OPEN (IP20)	SIGNATURES	DATE	 BENSHAW 615 ALPHA DRIVE PITTSBURGH, PA 15238 550 BRIGHT STREET LISTOWEL, ONTARIO N4W 3W3	REV 0
	THIS DRAWING AND ALL INFORMATION CONTAINED HEREIN, IS THE PROPERTY OF BENSHAW INC., AND MAY NOT BE REPRODUCED OR DIVULGED TO UNAUTHORIZED PERSONS WITHOUT THE EXPRESS WRITTEN CONSENT OF BENSHAW INC. IT IS PROVIDED SOLELY FOR THE CONVENIENCE OF THE USER AND SHALL BE RETURNED UPON REQUEST.				DRWN. RJF	03/31/20		
					CHKD. DRP	11/17/20		
					ENG. DRP	01/09/22		
					MFG.			
					SIZE	DWG NO.	VFD-RSI-040-H2-4C	
					SCALE: 1:1			SHEET 1 OF 1