


















Connections

Connections

Frame	Wire type	Main Terminal Size								Torque		
			(AWG / mm ²)						mm(max)	[lb-in]	[Nm]	[kgf·cm]
RC-9A		M4	18~10 / 1~6	18~10 / 1~6	18~10 / 1~6	9.6	20	2.25	23			
RC-12A			18~10 / 1~6	16~10 / 1~6	16~10 / 1~6							
RC-18A			18~10 / 1~6	16~8 / 1.5~10	16~8 / 1.5~10							
RC-22A			18~10 / 1~6	14~8 / 2.5~10	14~8 / 2.5~10							
RC-32A		M5	18~10 / 1~6	12~8 / 2.5~10	12~8 / 2.5~10	12.8	35	4	41			
RC-40A			18~10 / 1~6	8~6 / 10~16	8~6 / 10~16							
RC-50A		M6	-	10~4 / 6~25	10~4 / 6~25	14	35	4	41			
RC-65A			-	8~3 / 10~35	8~3 / 10~35							
RC-75A		M8	-	8~2 / 10~35	8~2 / 10~35	17	45	5.1	52			
RC-85A			-	8~1/0 / 10~50	8~1/0 / 10~50							
RC-100A			-	8~2/0 / 10~70	8~2/0 / 10~70							
RC-125A		M8	-	3~2/0 / 35~70	3~2/0 / 35~70	24.5	80	9.1	93			
RC-150A			-	3~4/0 / 35~95	3~4/0 / 35~95							
RC-6~150a Aux./Coil		M4	20~14 / 0.5~2.5	18~12 / 0.75~2.5	18~12 / 0.75~2.5	7.6	10	1.13	12			
RSC-180A		M10	-	1~4/0 / 50~95	1~4/0 / 50~95	25	130	14.7	150			
RSC-220A			-	1/0~300 / 50~150	1/0~300 / 50~150							
RSC-300A		M12	-	4/0~500 / 95~240	4/0~500 / 95~240	30	200	22.6	230			
RSC-400A			-	350~700 / 185~185x2	350~700 / 185~185x2							
RSC-600A		M16	-	350~800 / 185~240x2	350~800 / 185~240x2	40	500	56.5	576			
RSC-800A			-	700~Busbar	-							
RSC-180~800A Aux./Coil		M4	16~10 / 1.25~5.5	16~10 / 1.25~5.5	16~10 / 1.25~5.5	7.6	15	1.75	18			